Proof, Photo & Production media
PRODUCT DATASHEET

POWERED BY bestcolor technology

EFI Laser Magazin Print Paper 130 Semiglossy

PEFC
PEFC/04-31-1091

EFI Laser Magazin Print Paper 130 Semiglossy Double sided coated paper, for high quality prints, e.g. dummy production of magazines, short run production etc.
This paper has an excellent haptic feel due to its very smooth quality. It is very good foldable and therefore perfectly suitable for the above applications.

Description:

- Semiglossy paper
- Dry toner technology
- Printable both sides
- Suitable for most current colour copiers and laser printers
- Heat stable
- Optimum acceptance and adherance of toner

Application:

- Production
- Photo

Technical data:

- Weight	130	g/m²
- Thickness	115	µ
- Opacity	97	%
- Gloss [Tappi 75°]	27,5	%
- L*a*b* Paper white	94,5 / 1,3 / -4,9	
- Storage	15 - 30	°C (40 - 60% RH)

Size

Sheet

DIN A4	(210 x 297 mm)
SUPER A4	(241 x 340 mm)
DIN A3	(297 x 420 mm)
DIN A3ÜF	(305 x 457 mm)
SRA3	(320 x 450 mm)
SUPER A3(NOBI)	(328 x 453 mm)
DIN A3+	(330 x 483 mm)
	(311 x 457 mm)
DIN A2	(420 x 594 mm)

Tecco® living paper

Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.